



BIB'UP TOP 290

Description

BIB'UP model shown with roller table option

Semi-manual filling machine

BIB'UP TOP 290

Filling machine for separate BIB and POUCH vacuum bags, in a range of formats

Ergonomic and efficient, the BIB'UP TOP 290 filling machine is ideal for small and medium production runs of 1.5 to 20 litre BIB and 1.5 to 3 litre POUCH vacuum bags.

Easy to move or to use in a fixed position, fully equipped as standard, and with a wide range of options to suit your sector of activity, the BIB'UP TOP can fill up to 290 3L BIB bags per hour*, at high temperature, in a cold chain or at ambient temperature.

Exceptional quality-price-performance ratio!

***Depending on the characteristics of the product to be filled, the filling process, the options chosen and the machine operator's working conditions.**

Equipment complies with Machinery Directive 2006/42/CE. Conformity verified and validated by an independent body.

OPERATION AND DEGREE OF AUTOMATION

Complete filling cycle with manual and automated stages:

- Manual operations:

insertion of empty bag then, using an ergonomic lever arm: removal of tap, insertion of filling head into neck, launch of filling cycle

- Automated operations:

vacuum created in bag, filling and counting to programmed volume, nitrogen injection (if programmed)

- Final manual operations:

using ergonomic lever arm, repositioning of filling head, refitting and insertion of tap, and manual removal of the full bag

STANDARD IMMOBILISER & FILLING SAFETY

- Filling cycle cannot start if the head is not lowered into the neck of the bag

- Position sensor control

- Ergonomic lever arm locks automatically when filling begins

A guaranteed totally clean and safe filling process!

THE BEST QUALITY-PRICE-PERFORMANCE RATIO ON THE MARKET

- Filling machine with reliability demonstrated more than 1,000 times over
- Clean, simple, high-quality packaging guaranteeing optimum product shelf-life
- Easy to clean, programmable and automated
- Exceptional actual working speeds of up to 260 5L bags per hour
- The benefit of the quality of the Technibag network after-sales service
- A much higher than average resale value if you decide to further automate your BIB and/or POUCH packaging equipment

MORE INFO

[Print](#)

[Contact us](#)

Range of filling machines

SPEEDS

BIB/hour

	PUMP AL30/PUMP AL40	3 L	280 / 290
5 L	250 / 260		
10 L	200 / 210		
15 L	160 / 175		
20 L	140 / 150		

POUCH/hour

POMPE AL30 / POMPE AL40

1.5 L	260 / 270
3 L	240 / 250

According to manufacturer's data

BIB/hour

	PUMP AL30/PUMP AL40	3 L	280 / 290
5 L	250 / 260		
10 L	200 / 210		
15 L	160 / 175		

BIB/hour

20 L

140 / 150

POUCH/hour

POMPE AL30 / POMPE AL40

1.5 L

260 / 270

3 L

240 / 250

According to manufacturer's data

TECHNICAL CHARACTERISTICS

- **Electricity supply: 230 VAC 50 Hz 1P+N+E**
 - **Compressed air pressure required: 6 bar**
 - **Nitrogen pressure required: 0,5 bar**
 - **Liquid infeed connection: to be defined (40 MACON as standard)**
 - **Dimensions: Depth: 1000 mm / Height: 1560 mm / Width: 540 mm**
 - **Weight: 55 kg (without options)**
-
- **Electricity supply: 230 VAC 50 Hz 1P+N+E**
 - **Compressed air pressure required: 6 bar**
 - **Nitrogen pressure required: 0,5 bar**
 - **Liquid infeed connection: to be defined (40 MACON as standard)**
 - **Dimensions: Depth: 1000 mm / Height: 1560 mm / Width: 540 mm**
 - **Weight: 55 kg (without options)**

STANDARD CONFIGURATION – STANDARD EQUIPMENT

-
- Painted steel frame mounted on 4 castors with box shelf
 - Work surface: 304 stainless steel, tilt adjustable
 - 316 stainless steel liquid circuit for continuous use up to 90°C
 - AL30 side-channel pump, flow rate +/- 40 HL/h at filling head, 316 stainless steel body and turbine, with 2 total drainage valves and direction reverser
 - 40 MACON connector
 - 316 stainless steel filling head with integral closure and screw-on nozzle, integrated vacuum and nitrogen-injection circuits
 - Programmable and automated CIP circuit
 - Paddle-wheel flowmeter with 316 stainless steel body
 - Monochrome display, programme upload via micro USB cable. A configurable recipe for each filling volume, up to 6 recipes
 - T1 mechanical clamp for Vitop or equivalent taps, high neck
 - Immobiliser and filling safety
 - Options: please consult us
-
- Painted steel frame mounted on 4 castors with box shelf
 - Work surface: 304 stainless steel, tilt adjustable
 - 316 stainless steel liquid circuit for continuous use up to 90°C
 - AL30 side-channel pump, flow rate +/- 40 HL/h at filling head, 316 stainless steel body and turbine, with 2 total drainage valves and direction reverser
 - 40 MACON connector
 - 316 stainless steel filling head with integral closure and screw-on nozzle, integrated vacuum and nitrogen-injection circuits
 - Programmable and automated CIP circuit
 - Paddle-wheel flowmeter with 316 stainless steel body
 - Monochrome display, programme upload via micro USB cable. A configurable recipe for each filling volume, up to 6 recipes
 - T1 mechanical clamp for Vitop or equivalent taps, high neck
 - Immobiliser and filling safety
 - Options: please consult us

https://www.technibag.com/wp-content/uploads/2025/03/BIBUP-2.0_SICAREX-CHATEAU-DE-LECLAIR-NEW-LOGO-TBG.mp4

performance

In action

Don't just take our word for it,
see what our customers have to say!